

# PRODUCT DATA SHEET



## PNEUMATIC EQUIPMENT OILS

### PAL ROCKDRILL – L, H

These products are high performance mineral oil-based lubricant, specially developed for air lubrication of all type of pneumatically operated equipment's. The products meet the highest demands of operation thereby reducing oil consumption and extending the life of machine components. They provide optimum film strength, lubricity and good metal wetting characteristics. These oils have good flow characteristics which ensure proper feed and dispersion through the oilers.

These oils are formulated with a blend of refined base stocks and selected additives containing extreme pressure, tackiness, antiwear, antirust, anticorrosion antioxidant, and antifoam properties.

**Recommended** for lubrication of pneumatic equipment's like rock drills, jack hammers, wagon drills, chippers etc. They are also used in small in-plant pneumatic tools such as drills, tapers, impact wrenches grinders, filing tools, riveters and hoists etc.

CHARACTERISTICS			
S. NO.	PROPERTIES	ROCKDRILL-L	ROCKDRILL-H
1.	Appearance	Dark	Dark
2.	Kinematic Viscosity, cSt @100°C	11-13	15-18
3.	Relative Density, @30°C	0.88	0.93
4.	Flash Point, COC, °C min.	180	180

**\* The specifications are subject to variations/ development / customization.**

**PACKING:** 210L, 50L