

PRODUCT DATA SHEET



INDUSTRIAL ENGINE OILS

PAL HYLUBE - 40, 20W40

These are quality performance industrial engine oils, meeting API: SC/CC performance requirements, specially developed for lubrication of engines coupled with generators/industrial equipment's in SSI or Medium Scale Industries. They provide good detergent / dispersant properties which keeps the engine clean & good antiwear characteristics keep the rubbing surfaces well apart.

These oils are formulated from selected solvent refined base oils & combination of antioxidant, antiwear and detergent / dispersant additives.

Recommended for lubrication of diesel engines coupled with power generating sets/industrial equipment's, operating under moderate duty conditions.

PERFORMANCE LEVEL: IS 13656-2002(E-PL1/E-DL1), US MILITARY-MIL-L-2104B, API: SC/CC specifications.

CHARACTERISTICS			
S.NO.	PROPERTIES	PAL HYLUBE 40	PAL HYLUBE -20W40
1.	Kinematic Viscosity, cSt @100°C	13-16	13-16
2.	Viscosity Index, min.	95	110
3.	Pour Point, °C, max.	-6	-21
4.	Flash Point, COC, °C, min.	220	200
5.	TBN, mg KOH/gm.	4-5	4-5

* The specifications are subject to variations/ development / customization.

PACKING: PAL HYLUBE 40- 210L, 50L, 20L

PAL HYLUBE 20W40- 210L, 50L, 20L, 10L