

PRODUCT DATA SHEET



GENERAL PURPOSE FLUSHING OIL

PAL FLUSH

PAL FLUSH is formulated for flushing of engine, transmission and other lubrication systems after the old oil has been drained out. It is a blend of highly refined light mineral oil and detergent/dispersant additives to enhance removal of sludge and lacquers.

Recommended for use where a system's history is unknown or service fill lubricant may have been used beyond its oil drain interval / contamination problem.

Direction for use

- ❖ Warm up the oil by running the system till the oil reaches normal operating temperature.
- ❖ Open the drain plug and drain out the used oil.
- ❖ Fill the system with PAL FLUSH OIL between minimum and maximum level.
- ❖ Run the system without load for 5 to 10 minutes or till the oil reaches normal operating temperature and circulates throughout the system.
- ❖ Drain out the flushing charge and ensure that the system is free of sludge and lacquers or any other contamination. If the examination is not satisfactory, repeat the procedure.
- ❖ Refill the system with recommended lubricant.

CHARACTERISTICS		
S. NO.	PROPERTIES	PAL FLUSH
1	Kinematic Viscosity, cSt @ 40°C	21-23
2	Kinematic Viscosity, cSt @ 100°C	3-4
3	Specific gravity, Max.	0.901
4	Flash Point, COC, °C, Min.	170
5	Pour Point, °C, Max.	-3

* The specifications are subject to variations/ development / customization.

PACKING: 210L, 50L, 20L