PRODUCT DATA SHEET



MULTIGRADE DIESEL ENGINE OIL PHD-15W40 & PHD-20W40 (COMMANDER)

These oils are high quality performance **multigrade** engine oils, meeting API:CF/SF performance requirements, formulated from selected base oils and additives, to suit diesel engines.

PRODUCT FEATURES

- Optimum viscosity is maintained to provide effective lubrication.
- Special dispersant / detergent additives provide excellent piston cleanliness and reduce exhaust emission.
- Lower oil consumption and increased fuel efficiency.
- Quicker engine starts and longer battery life.
- Suitable for all seasons.

APPLICATIONS

Recommended for lubrication of all 4-stroke diesel engines / turbo charged engines of heavy vehicles and heavy earth moving machinery and power generating sets, operating under severe duty conditions.

PERFORMACNE LEVEL: IS13656-2002(E-DL3), API: CF and exceeds US MILITARY MIL-L-2104C, MACK T-7 specifications.

| CHARACTERISTICS | | | |
|-----------------|----------------------------------|----------------------|-------------|
| S.NO. | PROPERTIES | PHD 15W40 | PHD 20W40 |
| | | (COMMANDER) | (COMMANDER) |
| 1. | Appearance | Clear Golden Natural | Clear Red |
| 2. | Kinematic Viscosity, cSt @ 100°C | 12.5-16 | 12.5-16 |
| 3. | Viscosity Index, min. | 115 | 110 |
| 4. | Pour Point, °C, max. | -27 | -21 |
| 5. | Flash Point, COC, °C, min. | 200 | 200 |
| 6. | TBN, mg. KOH/gm. | 5-7 | 5-7 |

^{*}The specifications are subject to variations/development/customization.

PACKING: PHD 15W40 – 210L, 50L, 20L, 1L, 500ml

PHD 20W40 (COMMANDER) - 210L, 50L, 20L, 10L, 7.5L, 6L, 5L,1L